

AURORA
BOREALE

Expand your Brightness



SCAN TO VISIT OUR
WEBSITE

www.ablighting.ae

ABTECH Lighting Solutions


SPARTA

DATASHEET SPRL2

Recessed Linear light

SPARTA

SPRL2



Description

Rigid recessed linear LED luminaire with trim profile, providing seamless integration and uniform glare-free illumination for architectural applications.

Design Capability

- Flexible power (W) and lumen output configurations
- Wide CCT range (2700K–6500K, tunable white optional and RGB)
- Compatible with preferred LED modules and drivers (Tridonic, TCI, Philips)
- Custom lengths and continuous system configurations

Key Feature



- **Rigid Rectangular Profile**
ensuring precise, straight linear lighting



- **Uniform glare-free**
illumination with opal diffuser (~120° beam)



- **Recessed installation**
with trim for clean ceiling integration

Ideal Applications

- Offices and workspaces
- Corridors and circulation areas
- Meeting rooms and conference spaces
- Retail and commercial interiors
- Hospitality environments
- Continuous recessed ceiling lighting layouts

SPARTA

SPRL2

Beam Angle

120°

IP

20

Life time

5

Years

Shape


Rectangular

CRI

>80/90



Indicative Intensity Distribution Curve
Linear Light 40 mm | Opal PMMA | 120° Beam 0°



Voltage

220~240V

Diffuser

opal PMMA

Efficiency
lm/W

Up to **170 lumen/Watt**
from the light source

Dimming

On/Off, Dali, Phase Cut, 0-10V, 1-10V

Body Material

Extruded aluminum

Finishing Colors

☐ White ☐ Black ☐ Silver ☐ RGBW

Mounting




Pendant



Surface

CCT



Led Brand | Driver Brand


TCI LED

TRIDONIC PHILIPS

SPARTA

SPRL2

Dimension and Capacity



Dimensions (mm)


48 X 35 X 30

Power (Watt)

20W ~ 40w

Driver Location

External



Dimensions (mm)


60x35x50

Power (Watt)

20W ~ 40w

Driver Location

External



Dimensions (mm)


93.5 X 35 X 70

Power (Watt)

40w ~ 80w

Driver Location

External



Dimensions (mm)

123 X 35 X 96

Power (Watt)

60W ~ 120w

Driver Location

External

AUROLA
BOREALE

